



Eupen, 22/04/2009

**TECHNICAL SPECIFICATIONS**

	Target value	Unit	tolerance
Foam type	<b>DB25X/</b>		
Color	<b>anthr.</b>		
Width	<b>205 / 220</b>	cm	+2/+4 cm
Color	<b>grey</b>		
Width	<b>216 / 220</b>	cm	+2/+4 cm
Height	<b>102</b>	cm	-0/+5 cm
Density gross	<b>25,0</b>	kg/m <sup>3</sup>	+/- 5 %
Density net	<b>23,0</b>	kg/m <sup>3</sup>	+/- 5 %
Compression hardn.	<b>105</b>	N	+/- 10 %
ISO 2439-1998	<b>130</b>	N	+/- 10 %
	<b>250</b>	N	+/- 12,5 %
Tensile strength	<b>100</b>	Kpa	min.
ISO 1798-1997			
Elongation at break	<b>200</b>	%	min.
ISO 1798-1997			
Compression load deflection	<b>3,10</b>	Kpa (40%)	+/- 10 %
ISO 3386-1			
Compression set	<b>7,0</b>	%	max.
ISO 1856-2000			
Fire behaviour	<b>MVSS 302 SE</b>		

Our foam types are free from CFC, HCFC and Formaldehyde.

J.-P. Doeuillet  
Qualityoffice