

XD1C1

1/2


VDE Code: A-DQ(ZN)2Y(SR)2Y



Non-metallic outdoor fibre optic cable, rodent resistant

Applications and features

- Outdoor cable with corrugated steel tape armour for direct burial and rodent protection
- Longitudinally water blocked with swelling elements
 - Loose tube, fully filled with thixotropic water-blocking gel



Design

1. FRP central strength element
2. Optical fibres
3. Gel-filled tube
4. Filler
5. Swelling elements
6. Wrapping tape
7. Rip cords
8. Tensile elements
9. PE inner sheath
10. Corrugated steel tape
11. PE outer sheath

Product description

This armoured outdoor cable contains from 5 to 12 loose tubes, stranded around a fibre-reinforced plastic (FRP) central element. If the fibres occupy fewer than 5 tubes the remaining positions are taken by fillers. Each tube contains up to 12 fibres in a special thixotropic water-blocking gel. Tubes and fibres are identified by a colour code.

The swelling elements ensure the longitudinal water blocking. The corrugated steel tape armour, placed between the inner and the outer sheath, protects the fibres from rodent attack and high compression forces.



XD1C1

Mechanical Specifications

XD1C1						
Number of fibres (*)	up to 36	up to 60	72	96	120	144
Number of tubes	6	5	6	8	10	12
Fibre per tubes (max.)	6	12	12	12	12	12
Tube diameter (mm)	2.1	2.8	2.8	2.8	2.8	2.8
Cable diameter, approx. (mm)	14.5	15.5	16.5	18.5	20	22
Inner sheath thickness (mm)	1.0					
Outer sheath thickness (mm)	1.5					
Weight, approx. (kg per km)	160	185	205	250	305	360
Max. pulling force during (**)						
- installation (N)	3.000	3.500	4.500	4.500	5.000	6.000
- operation (N)	2.000	2.000	2.500	3.000	3.000	3.500
Crush resistance (N/10cm)	6.000					
Min. bending radius						
- with tensile load	20 x cable diameter					
- without tensile load	15 x cable diameter					
Temperature range						
- operation	- 30°C to + 60°C					
- storage	- 40°C to + 70°C					
Tested according to	IEC 60794-1					

(*) other fibre numbers by request
(**) higher pulling force by request

Marking

"EUPEN + Product code + Fibre number/type + metric marking"

Lengths

Standard lengths: 2.000 m or 4.000 m, +/- 2%
Engineered lengths: by request

